

Condition assessment using PIPE PENETRATING RADAR: the Harvard Gulch Interceptor Denver case study

Csaba Ékes, PhD, PGeo

President - SewerVUE Technology Corp.

Jeff Maier, PE

Metro Wastewater Reclamation District



CCTV


- Visual only
- Qualitative
- Operator dependent
- Often unreliable, especially in large dia. trunks and interceptors
- E.g. 9' x 8' outfall sewer collapse in Washington DC in 2010
2 years after CCTV inspection
- Cause of collapse: external corrosion

REFERENCE



Is there a technology to see through the pipes and detect voids before they become sinkholes?

PPR Principle




A high frequency EM wave (25 MHz to 2.5 GHz), is emitted via an antenna into the ground or structure under evaluation.

The reflected energy caused by changes in the electromagnetic properties of the material is detected by a receiver antenna and recorded for subsequent analysis.

Antennas have to have direct contact with pipe wall.

PPR Deployment



Robotic PPR Inspection




- Remotely operated robot:
- HD CCTV (pan, tilt, zoom)
- 18-42 inch
- 9 to 3 o'clock
- 1500 feet tether (6000 ft optional)
- 2 auxiliary cameras
- LIDAR and sonar
- 3D LiDAR
- Accurate x,y,z coordinates
- 30 ft/min
- “Swiss army knife”

Robotic PPR Inspection




- PPR can confirm visual defects, map voids
- Measure rebar cover and/or concrete thickness
- Provides structural assessment, allows proactive asset management



ASCE | PIPELINES 2012 CONFERENCE

PPR Display and Reporting





3D Display


Block views of PPR traces that are recorded at different positions on the pipe surface

3D view of a 42" RC pipe joint, white bands and lines represent rebar.

PPR Display and Reporting







**Harvard Gulch Interceptor
multisensory robotic pipe condition
survey including
Pipe Penetrating Radar
laser and CCTV
Denver, CO**

Metro Wastewater Reclamation District's

Advanced Pipe Condition Assessment Technology Evaluation Program

Multi-Sensor Technologies Demonstrated & Evaluated:

- RedZone Responder
- CleanFlow HD Profiler (now owned by RedZone)
- SewerVue Pipe Penetrating Radar




Advanced Pipe Condition Assessment Technology Evaluation Program


Goals:

- Identify technologies that provide better condition assessment info than coring & CCTV
- Evaluation of effectiveness & accuracy
- Better information = Better decision making
- Intelligent prioritization of pipe rehabilitation needs & funding allocation



Evolution of Pipe Condition Assessment Technology









ASCE | PIPELINES 2012 CONFERENCE





ASCE | PIPELINES 2012 CONFERENCE




Depth Verification









- Several 1000 data points (every inch)



Summary

Pipe wall thickness

- Uniform, no significant pipe wall loss: 2.5-3.3" with an average of 3.0"

Rebar Cover

- Range of 0.25" and 3.2"
- Locations with less than 0.53" rebar were identified
- Loss of rebar cover due to pipe manufacturing process & not result of pipe wall loss
- PPR mapped grout thickness within the casing pipe
- LIDAR results show significant pipe wall erosion at flow level

Results & Accuracy Correlation

- SewerVue PPR data accuracy levels exceeded 98% when compared directly to physical concrete core sample measurements.
- SewerVue provided MWRD with information about remaining pipe thickness, rebar integrity and the ability to check for corrosion & voids behind the pipe, unique to PPR technology.
- Accuracy comparable to other advanced multi-sensor pipe condition assessment technologies.

Questions and Contact



Booth 207

**1 888 9 SEWERVUE
(1 888 973 9378)**

**www.sewervue.com
info@sewervue.com**

**Jeff Maier
303 286 3285
jmaier@mwrddst.co.us**

ASCE | PIPELINES 2012 CONFERENCE